

Flexible One Output VGA card with Audio

Seamless one output VGA card with PCM audio

MPN: FLEX-OUT-VGA



FEATURES

- Single one output seamless VGA (YPbPr, C-video and S-video) card
- Stereo analog audio output
- Supported resolutions: 1920x1200, 1080p/60
- Plug & play, easily fits in to the FLEX-MMX series
- Backed by KanexPro 3-Year full parts & labor warranty

SPECIFICATIONS

Output: 1xVGA, 1xAudio Connectors: Female 15 pin HD, 1x3-pin pluggable terminal block Video Signal: VGA, CVBS, YPbPr Output Resolutions: VGA: 800x600, 1024x768, 720p, 1280x1024, 1080i, 1080p, 1920x1200 Power Consumption: 4.6w Switching Speed: ?100ns CVBS: 480i, 576i @ 6.75Gbps Working Temperature: 32-122 °F Reference Humidity: 10%-90%





The KanexPro FLEX-OUT-VGA

is a seamless one Output VGA card with analog audio output compatible with YPbPr, C-video and S-video signals designed for FLEX-MMX chassis supporting video resolutions up to 1080p/60 HD and PC resolutions up to 1920x1200@60Hz. The card is compliant to HDCP and supports EDID management from the switcher.

Applications:

Ideally used in command and control centers, simulation centers, large AV conference rooms for up-to-second viewing of critical information and high – resolution imagery.