1405 Pioneer St., Brea, CA 92821 888.975.1368 info@kanexpro.com

# Composite/ S-video to 4K HDMI® Converter

Convert Legacy Composite AV or S-Video signals to 4K UHD

MPN: CON-AV-HD4K

The KanexPro CON-AV-HD4K is a universal scaler converter designed to up-scale one Composite (RCA) or S-video input to HDMI 4Kx2K@60Hz output. The CON-AV-HD4K is capable of converting analog to digital formats with multiple adjustments and range to achieve the most ideal video image using the front panel buttons for scaling & zoom. It is portable and simple plug and play device making it the most ideal converters for scaling analog to 4K digital signal conversion.

Perfect for older AV devices that need to be transformed to 4K UHD display for viewing purposes only.

## **FEATURES**

- Scale & Convert S-Video / Composite Video to UltraHD 4K display
- Built-in scaler to upscale video resolutions up to 4K@60Hz
- Supports PAL, NTSC3.58, NTSC4.43, SECAM, PAL/M, and PAL/N input format
- Advanced signal processing with great precision, colors & details
- - Selective Source button to switch between analog
  - Selective Resolution and Zoom button to get the best optimal resolution
  - Easy firmware update via Micro-USB
  - 5V DC external power supply included

### **SPECIFICATIONS**

#### Interface:

- Input ports: 1 x RCA (Yellow, White, Red). 1x S-Video, 1 x Min- USB
- Output ports: 1 x HDMI

#### Video Resolutions Support:

- C-Video /S-VIDEO input: PAL, NTSC3.58, NTSC4.43, SECAM, PAL/M, and PAL/N standard TV formats
- HDMI Output resolution: 4Kx2K@60Hz, 4Kx2K@30Hz, 1080p@60Hz, & 720p@60Hz

#### General:

- Operating Temperature: 0°C ~ 40°C / 32°F ~ 104°F • Storage Temperature: -20°C ~ 60°C / -4°F ~

140°F

• Relative Humidity: 20 ~ 90% RH (Non-

condensing)

• Power Consumption (Max): 3W

3 8kV (air-gap discharge) ESD Protection: • Human Body Model: 3 4kV (contact discharge)

• Dimensions: 3.66" x (D) 3.33" x (W) x 1.1" (H)

· Weight: 0.66 lbs



ABOUT KANEXPRO