1405 Pioneer St., Brea, CA 92821 888.975.1368 info@kanexpro.com

# VGA 1x1 Extender over CAT5e/6 with Audio up to 1,000ft (300m)

Extend high-resolution VGA signals over a single CAT5e/6 cable

MPN: VGAEXTX1



# The KanexPro VGA extender over a single CAT5e/6 cable

is designed for routing highresolution VGA signals and stereo audio over remote distances up to 1,000ft. (300m). Each receiver set features a separate gain and peaking rotary switch used in adjusting brightness and skew over long distances.

The 15-pin HD connectors are convenient and cost-effective for all input/ output connections supporting full bandwidth compatible from VGA to WUXGA graphics card resolutions and HDTV's to projectors. In addition, each output performs a separate buffering to maintain signal integrity and reject noise interference.

#### **FEATURES**

- Extend high-resolution VGA signal with audio over a single Cat5E/6 cable up to 1,000 feet (300m)
- Adjust GAIN and PEAK levels to adapt for variable lengths of UTP cable on the receiver
- Supports maximum resolutions up to WUXGA (1920x1200@60Hz)
- Stereo Audio Input through 3.5mm jack
- CAT5e/6 Output via RJ-45 Jack
- Transmitter includes Local VGA Monitor Output w/ 3.5mm jack
- EDID Compliant

Dimensions:

- Rack or under-desk mountable
- 5VDC external power supply included

• Storage Humidity: 5% to 90 % RH (no

• Regulatory Approvals Converter: FCC, CE, UL

VGA Extender: 4"x2.6"x1" (102x66x25.5mm)

Receiver: 3.25"x1.4"x0.8" (82.6x35.6x20mm)

• Regulatory Approvals Power Supply: FCC, CE, UL

#### **SPECIFICATIONS**

## • Transmitter (1)

Input: VGA x1/3.5mm Stereo x1 Output: Cat 5e/6 x1/VGA Output (Local) x1/3.5mm Stereo x1

### • Receiver (1)

Input: Cat 5e/6 x1

Output: VGA x1/3.5mm Stereo x1

- Vertical Frequency Range: 60/75/85Hz
- Resolutions (PC): VGA-WUXGA (1920x1200@60Hz)
- Power Supply: 5V DC@2A, 5W
- $\bullet$  Operating Temperature: 0°C to +70°C
- Operating Humidity: 10% to 85 % RH (no condensation)
- Storage Temperature: -10°C to +80°C
- Total Weight: VGA Extender: 0.47lbs (215a)

Receiver: 0.25lbs (115g)

• Warranty: 1 Year parts and labor

Source Display

