

4x2 HDMI/USB-C 4K60 Seamless Presentation Switch with HDBaseT 3.0 70m Out

4K60 4:4:4 Multiview Switcher with USB-C 60W PD, USB 3.2 KVM, Dante® Audio & HDBaseT 3.0

MPN: SW-4X2PS-70M



Seamless 4K60 presentation switching with multiview, USB-C connectivity, KVM control, and HDBaseT 3.0 extension — in a single half-rack unit. The KanexPro SW-4X2PS-70M is a 4x2 seamless presentation switch that routes four video sources (2x USB-C, 2x HDMI) to two HDMI outputs plus one HDBaseT 3.0 output at resolutions up to 4K@60Hz 4:4:4 with HDCP 2.3 compliance.

Multiple multiview display modes (PIP, PBP, Triple, Quad, Custom) allow simultaneous viewing of up to four sources on a single screen. USB-C inputs deliver DisplayPort Alt Mode A/V, USB 3.2 Gen 1 data, and 60W power delivery. Built-in audio DSP with Dante® 2x2 I/O, USB 3.2 KVM switching with keyboard/mouse hotkeys, and HDBaseT 3.0 extension up to 70m complete an integrated conferencing and presentation solution. Control via front panel, IR remote, RS-232, TCP/IP, or Web GUI.

| | | | | |
|---|---|---|--|---|
|  4K60 4:4:4 HDCP 2.3 18 Gbps |  Multiview PIP / PBP Quad / Custom |  USB-C 60W PD USB 3.2 / DP |  HDBaseT 3.0 — 70m 4K60 @ 40m |  Dante® 2x2 Audio DSP / EQ |
|---|---|---|--|---|

KEY FEATURES

- Routes 2x USB-C and 2x HDMI sources to 2 HDMI outputs at up to 4K@60Hz 4:4:4 with HDCP 2.3 and 18 Gbps bandwidth
- Multiview display modes: Auto, Single, PIP, PBP, Triple, Quad, and 5 Custom layouts with seamless switching
- USB-C inputs support DP Alt Mode A/V, USB 3.2 Gen 1 (5 Gbps), 1G LAN passthrough, and 60W PD charging per port
- HDBaseT 3.0 output (mirrored with HDMI OUT 2) extends uncompressed 4K60 4:4:4 up to 40m or 1080p/4K30 up to 70m via CAT6A
- USB 3.2 KVM switching with keyboard and mouse hotkey support; USB 2.0 extension to receiver over HDBaseT
- Built-in audio DSP with mixing, matrixing, 31-band GEQ, volume, delay, and Dante® 2x2 audio I/O
- CEC and RS-232 display power control; advanced EDID management (17 modes); 8 preset scenes
- Control via front panel buttons, IR remote, RS-232, TCP/IP (Web GUI) — included HDBaseT receiver with PoE

SPECIFICATIONS

| | |
|-----------------------------|---|
| HDMI / HDCP / DP | HDMI 2.0b • HDCP 2.3 • DP 1.4 |
| Video Resolution | Up to 4K@60Hz 4:4:4 • 18 Gbps |
| Multiview Modes | Auto, Single, PIP, PBP, Triple, Quad, Custom (5) |
| Audio | Digital LPCM 2CH • Analog balanced/unbalanced • Dante® 2x2 |
| TX Video I/O | 2x USB-C + 2x HDMI In • 2x HDMI + 1x HDBT Out |
| USB-C Features | DP Alt Mode • USB 3.2 • 60W PD • 1G LAN |
| USB / KVM | USB 3.2 Gen 1 (5 Gbps) • KVM with hotkeys • USB 2.0 over HDBT |
| HDBaseT 3.0 Distance | 4K60: 40m • 1080p/4K30: 70m (CAT6A F/FTP) |
| Control | Front Panel • IR • RS-232 • TCP/IP • Web GUI |
| Enclosure / Power | 220x220x44.5 mm (TX) • DC 24V/8A • 170W max |
| Environment | 32–104°F (0–40°C) • 20–80% RH |

PACKAGE CONTENTS

- 1x Presentation Switch • 1x HDBaseT Receiver • 1x IR Blaster Cable • 1x IR Receiver Cable • 3x 3-pin Phoenix • 3x 5-pin Phoenix • 4x Mounting Ears • 8x Screws • 1x 24V/8A Power Supply • 1x IR Remote • 1x Product Manual



Scan for product page

kanexpro.com/item/SW-4X2PS-70M

sales@kanexpro.com | www.kanexpro.com