

4K60Hz HDMI Cascading Extender Receiver over Cat6 — 70M

Add-on RX for EXT-HDMICAS70M | 4K@60Hz | Per-Display EDID | 3-Year Warranty
 MPN: EXT-HDMICAS70MRX



The KanexPro EXT-HDMICAS70MRX is the add-on receiver unit for the EXT-HDMICAS70M cascading HDMI extender system. Each unit adds one additional display location to an existing cascading installation — up to 9 additional receivers per TX, for a total of 10 display endpoints from a single source.

Each EXT-HDMICAS70MRX independently manages the connected display's resolution and EDID, auto-adapting for mixed-resolution environments. Bi-directional IR control and ARC S/PDIF audio de-embed are included on every unit. Requires EXT-HDMICAS70M transmitter kit. Backed by KanexPro's 3-year warranty.

 Add-on RX EXT-HDMICAS70M	 4K@60Hz Auto EDID	 70M Cat6 Single Cable	 IR Bi-dir ARC S/PDIF	 3-Year Warranty
---	--	--	---	--

KEY FEATURES

- Add-on receiver unit for the EXT-HDMICAS70M cascading extender system — sold separately
- Supports 4K@60Hz HDR over single Cat6/6a/7 up to 70M per run
- Independently manages display resolution and EDID — auto-adapts to connected display
- HDCP 2.2 support
- Bi-directional IR pass-through (20–60KHz) — IR blasters included
- ARC S/PDIF digital audio de-embedded output
- Plug-and-play — no configuration required
- Compact aluminum chassis: 106×99×26.2mm, 210g
- 3-year KanexPro parts and labor warranty

SPECIFICATIONS

Type	Add-on RX unit — pairs with EXT-HDMICAS70M
HDMI	2.0 HDCP 2.2
Max Resolution	4K×2K@60Hz (4:4:4 HDR)
Cable	Single Cat6 / Cat6a / Cat7
Max Distance	70M (230 ft.) per Cat6 run
EDID	Independent per-receiver management
IR	Bi-directional 20–60KHz (blasters included)
Audio	ARC S/PDIF de-embedded
Power	DC 5V–12V RX <4W
Dimensions	106×99×26.2mm
Weight	RX 210g
Temp	Operating: -20–60°C Storage: -30–70°C



Scan for product page

[kanexpro.com/item/EXT-HDMICAS70MRX](https://www.kanexpro.com/item/EXT-HDMICAS70MRX)

sales@kanexpro.com | www.kanexpro.com