

## 4K60 HDBaseT Input Card for Flex Matrix Pro

4-Port CAT Input — 330ft Extension, PoC, Dante/AES67 & TAA

MPN: FLEX-PROCAT-IN



Add four CAT (HDBaseT 3.0) inputs to any Flex Matrix Pro chassis. The FLEX-PROCAT-IN delivers 4K60 4:4:4 at 18Gbps with HDCP 2.2, HDR, scaling, and Dante/AES67 per port.

Seamless switching. EDID/HDCP management. Hot-swappable. TAA compliant. 330ft (100m) via CAT6A. PoC supported.

 <b>4× CAT</b> 330ft Input PoC	 <b>4K60</b> 18Gbps HDCP 2.2	 <b>Dante</b> AES67 Audio	 <b>Hot-Swap</b> Zero Downtime	 <b>TAA</b> Compliant
--	--	---	---	--

### KEY FEATURES

- 4× CAT (HDBaseT 3.0) inputs — hot-swappable across all Flex Pro chassis (16×16 to 128×128)
- 4K60 4:4:4 at 18Gbps • HDCP 2.2 • HDR
- Dante/AES67 network audio • 8ch LPCM High-Res Audio
- Independent scaling per input • seamless switching • EDID/HDCP management
- 330ft (100m) uncompressed 4K60 via CAT6A • PoC • bi-directional RS-232
- Hot-swappable • TAA compliant

### SPECIFICATIONS

<b>Ports</b>	4× CAT (HDBaseT 3.0) inputs
<b>Resolution</b>	4K60 4:4:4
<b>Bandwidth</b>	18Gbps
<b>Audio</b>	8ch LPCM, Dante/AES67
<b>Extension</b>	330ft (100m) via CAT6A
<b>PoC</b>	Supported
<b>Switching</b>	Seamless
<b>Compatibility</b>	All Flex Pro chassis
<b>Compliance</b>	TAA • Hot-swappable

### PACKAGE CONTENTS

1× FLEX-PROCAT-IN

