

4K60 HDBaseT Output Card for Flex Matrix Pro

4-Port CAT Output — 330ft Extension, PoC, Dante/AES67 & TAA

MPN: FLEX-PROCAT-OUT



Add four CAT (HDBaseT 3.0) outputs to any Flex Matrix Pro chassis. The FLEX-PROCAT-OUT delivers 4K60 4:4:4 at 18Gbps with HDCP 2.2, HDR, scaling, and Dante/AES67 per port.

Seamless switching. EDID/HDCP management. Hot-swappable. TAA compliant. 330ft (100m) via CAT6A. PoC supported.

 4× CAT 330ft Output PoC	 4K60 18Gbps HDCP 2.2	 Dante AES67 Audio	 Hot-Swap Zero Downtime	 TAA Compliant
---	--	---	---	--

KEY FEATURES

- 4× CAT (HDBaseT 3.0) outputs — hot-swappable across all Flex Pro chassis (16×16 to 128×128)
- 4K60 4:4:4 at 18Gbps • HDCP 2.2 • HDR
- Dante/AES67 network audio • 8ch LPCM High-Res Audio
- Independent scaling per output • seamless switching • EDID/HDCP management
- 330ft (100m) uncompressed 4K60 via CAT6A • PoC • bi-directional RS-232
- Hot-swappable • TAA compliant

SPECIFICATIONS

Ports	4× CAT (HDBaseT 3.0) outputs
Resolution	4K60 4:4:4
Bandwidth	18Gbps
Audio	8ch LPCM, Dante/AES67
Extension	330ft (100m) via CAT6A
PoC	Supported
Switching	Seamless
Compatibility	All Flex Pro chassis
Compliance	TAA • Hot-swappable

PACKAGE CONTENTS

1× FLEX-PROCAT-OUT



Scan for product page

[kanexpro.com/item/FLEX-PROCAT-OUT](https://www.kanexpro.com/item/FLEX-PROCAT-OUT)

sales@kanexpro.com | www.kanexpro.com