

4K60 CAT-to-HDMI Receiver for Flex Matrix Pro






HDBaseT 3.0 RX — 330ft over CAT6A with PoC, RS-232 & TAA

MPN: FLEX-PROCAT-RX



Place a display up to 330ft from the chassis. The FLEX-PROCAT-RX converts HDBaseT 3.0 back to HDMI with PoC and bi-directional RS-232. Connects to FLEX-PROCAT-OUT. 4K60 4:4:4, 18Gbps, HDCP 2.2.

EDID/HDCP management. Seamless switching. TAA compliant.

 RX CAT → HDMI 330ft	 4K60 18Gbps HDCP 2.2	 Dante AES67 Audio	 PoC Chassis Powered	 TAA Compliant
---	--	---	---	--

KEY FEATURES

- 4K60 4:4:4 at 18Gbps • HDCP 2.2 • HDR
- 330ft (100m) over single CAT6A • PoC from chassis
- Bi-directional RS-232 for endpoint control
- EDID/HDCP management • seamless switching
- TAA compliant

SPECIFICATIONS

I/O	1× HDMI + 1× RJ45 (CAT6A)
Distance	330ft (100m)
Power	PoC or DC 12V, 10W
RS-232	Bi-directional (Phoenix)
Resolution	4K60 4:4:4, 18Gbps
Compliance	HDMI 2.0, HDCP 2.2, TAA

PACKAGE CONTENTS

1× FLEX-PROCAT-RX



Scan for product page

kanexpro.com/item/FLEX-PROCAT-RX