

## 4K60 HDMI-to-CAT Transmitter for Flex Matrix Pro

HDBaseT 3.0 TX — 330ft over CAT6A with PoC, RS-232 & TAA

MPN: **FLEX-PROCAT-TX**



Place an HDMI source up to 330ft from the chassis. The FLEX-PROCAT-TX converts HDMI to HDBaseT 3.0 over CAT6A with PoC and bi-directional RS-232. Connects to FLEX-PROCAT-IN. 4K60 4:4:4, 18Gbps, HDCP 2.2.

EDID/HDCP management. Seamless switching. TAA compliant.

 <b>TX</b> HDMI → CAT 330ft	 <b>4K60</b> 18Gbps HDCP 2.2	 <b>Dante</b> AES67 Audio	 <b>PoC</b> Chassis Powered	 <b>TAA</b> Compliant
---	--	---	---	--

### KEY FEATURES

- 4K60 4:4:4 at 18Gbps • HDCP 2.2 • HDR
- 330ft (100m) over single CAT6A • PoC from chassis
- Bi-directional RS-232 for endpoint control
- EDID/HDCP management • seamless switching
- TAA compliant

### SPECIFICATIONS

<b>I/O</b>	1× HDMI + 1× RJ45 (CAT6A)
<b>Distance</b>	330ft (100m)
<b>Power</b>	PoC or DC 12V, 10W
<b>RS-232</b>	Bi-directional (Phoenix)
<b>Resolution</b>	4K60 4:4:4, 18Gbps
<b>Compliance</b>	HDMI 2.0, HDCP 2.2, TAA

### PACKAGE CONTENTS

1× FLEX-PROCAT-TX



Scan for product page

kanexpro.com/item/FLEX-PROCAT-TX