

4K60 Fiber Optic Output Card for Flex Matrix Pro

4-Port Fiber Output — 2km Singlemode / 300m Multimode — Dante/AES67 & TAA

MPN: FLEX-PROFIB-OUT



Add four Fiber Optic (LC) outputs to any Flex Matrix Pro chassis. The FLEX-PROFIB-OUT delivers 4K60 4:4:4 at 18Gbps with HDCP 2.2, HDR, scaling, and Dante/AES67 per port.

Seamless switching. EDID/HDCP management. Hot-swappable. TAA compliant. Singlemode 2km. Multimode 300m.

 4× Fiber 2km SM Output	 4K60 18Gbps HDCP 2.2	 Dante AES67 Audio	 Hot-Swap Zero Downtime	 TAA Compliant
--	--	---	---	--

KEY FEATURES

- 4× Fiber Optic (LC) outputs — hot-swappable across all Flex Pro chassis (16×16 to 128×128)
- 4K60 4:4:4 at 18Gbps • HDCP 2.2 • HDR
- Dante/AES67 network audio • 8ch LPCM High-Res Audio
- Independent scaling per output • seamless switching • EDID/HDCP management
- Singlemode 6,562ft (2km) • Multimode 984ft (300m) • adaptive SM/MM
- Hot-swappable • TAA compliant

SPECIFICATIONS

Ports	4× Fiber Optic (LC) outputs
Resolution	4K60 4:4:4
Bandwidth	18Gbps
Audio	8ch LPCM, Dante/AES67
Singlemode	6,562ft (2km)
Multimode	984ft (300m)
Switching	Seamless
Compatibility	All Flex Pro chassis
Compliance	TAA • Hot-swappable

PACKAGE CONTENTS

1× FLEX-PROFIB-OUT



Scan for product page

kanexpro.com/item/FLEX-PROFIB-OUT