

## 12G-SDI Input Card for Flex Matrix Pro

4-Port 12G/6G/3G/HD-SDI Input at 11.88Gbps — Dante/AES67 & TAA

MPN: FLEX-PROSDI-IN



Add four 12G-SDI (BNC) inputs to any Flex Matrix Pro chassis. The FLEX-PROSDI-IN delivers 4K60 4:4:4 at 11.88Gbps with SMPTE/ITU compliance, scaling, and Dante/AES67 per port.

Seamless switching. EDID/HDCP management. Hot-swappable. TAA compliant. 12G/6G/3G/HD-SDI auto-adaptation.

 <b>12G-SDI</b> 4-Port Input	 <b>4K60</b> 18Gbps HDCP 2.2	 <b>Dante</b> AES67 Audio	 <b>Hot-Swap</b> Zero Downtime	 <b>TAA</b> Compliant
--	--	---	---	--

### KEY FEATURES

- 4× 12G-SDI (BNC) inputs — hot-swappable across all Flex Pro chassis (16×16 to 128×128)
- 4K60 4:4:4 at 11.88Gbps • HDCP 2.2 • HDR
- Dante/AES67 network audio • 8ch LPCM High-Res Audio
- Independent scaling per input • seamless switching • EDID/HDCP management
- 12G/6G/3G/HD-SDI • up to 11.88Gbps • SMPTE/ITU auto-adaptation • auto reclocking
- Hot-swappable • TAA compliant

### SPECIFICATIONS

<b>Ports</b>	4× 12G-SDI (BNC) inputs
<b>Resolution</b>	4K60 4:4:4
<b>Bandwidth</b>	11.88Gbps
<b>Audio</b>	8ch LPCM, Dante/AES67
<b>SDI Standards</b>	12G/6G/3G/HD-SDI
<b>Data Rate</b>	11.88Gbps
<b>Switching</b>	Seamless
<b>Compatibility</b>	All Flex Pro chassis
<b>Compliance</b>	TAA • Hot-swappable

### PACKAGE CONTENTS

1× FLEX-PROSDI-IN

