

12G-SDI Output Card for Flex Matrix Pro

4-Port 12G/6G/3G/HD-SDI Output at 11.88Gbps — Dante/AES67 & TAA

MPN: FLEX-PROSDI-OUT



Add four **12G-SDI (BNC) outputs** to any **Flex Matrix Pro chassis**. The FLEX-PROSDI-OUT delivers 4K60 4:4:4 at 11.88Gbps with SMPTE/ITU compliance, scaling, and Dante/AES67 per port.

Seamless switching. EDID/HDCP management. Hot-swappable. TAA compliant. 12G/6G/3G/HD-SDI auto-adaptation.

 12G-SDI 4-Port Output	 4K60 18Gbps HDCP 2.2	 Dante AES67 Audio	 Hot-Swap Zero Downtime	 TAA Compliant
---	--	---	---	--

KEY FEATURES

- 4× 12G-SDI (BNC) outputs — hot-swappable across all Flex Pro chassis (16×16 to 128×128)
- 4K60 4:4:4 at 11.88Gbps • HDCP 2.2 • HDR
- Dante/AES67 network audio • 8ch LPCM High-Res Audio
- Independent scaling per output • seamless switching • EDID/HDCP management
- 12G/6G/3G/HD-SDI • up to 11.88Gbps • SMPTE/ITU auto-adaptation • auto reclocking
- Hot-swappable • TAA compliant

SPECIFICATIONS

Ports	4× 12G-SDI (BNC) outputs
Resolution	4K60 4:4:4
Bandwidth	11.88Gbps
Audio	8ch LPCM, Dante/AES67
SDI Standards	12G/6G/3G/HD-SDI
Data Rate	11.88Gbps
Switching	Seamless
Compatibility	All Flex Pro chassis
Compliance	TAA • Hot-swappable

PACKAGE CONTENTS

1× FLEX-PROSDI-OUT



Scan for product page

kanexpro.com/item/FLEX-PROSDI-OUT

sales@kanexpro.com | www.kanexpro.com